


Jar Collar Insert package specialty project

ex2-1247 / LETTER / Parts overview - NOT A CUTTING SHEET

USE THE FOLLOWING PATTERN SHEETS AT ACTUAL SIZE.

These miniature views identify the supplied patterns; they are deliberately reduced.



1. Pattern 1

1 pattern sheet supplied. Printed details are not cut lines unless explicitly marked.

Solid cut boundary / dashed score / shaded joining area. Read the full instructions.

Dry-fit the parts before gluing. Keep this overview beside the full-size pattern sheets.





Print at actual size / 100%. Disable fit-to-page.
Use the paper edition that matches the printer tray.

Jar Collar Insert package specialty project

ex2-1247 / LETTER / Pattern 1

Jar Collar



Print at actual size / 100%. Disable fit-to-page.
Use the paper edition that matches the printer tray.

Jar Collar Insert package specialty project

ex2-1247 / LETTER / Instructions

PURPOSE

Jar Collar Insert package specialty project developed as a fixed-size paper pattern with separate cut, fold and joining marks. Use the stated drawing sizes and make an empty trial before choosing material or contents.

DRAWING FACTS

- Square collar: 95 x 95 mm with 55 mm nominal circular opening and an access slit.

MATERIALS

Plain paper for a first trial, a ruler, scissors and a blunt scoring tool; adult help for internal cuts.

HOW TO USE THESE PAGES

1. Cut the square perimeter, 55 mm circular opening and access slit to the edge.
2. Open the slit gently and fit the collar around a suitable trial neck. Keep the paper away from contents and wet surfaces.
3. Close the access slit with a removable seal if needed. Measure the actual neck before using the intended container.

LIMITS AND CHECKS

- Nominal drawing dimensions are not a tested usable-capacity, load, mailing, food-contact or archival specification.
- Do not place valuable, wet, hot or breakable items in an unreviewed paper prototype.
- Trial: Measure the 50 mm reference and at least two named panel dimensions.
- Trial: Assemble an empty plain-paper trial; record closure, seam, clearance and material behavior.



50 mm print check

Print at actual size / 100%. Disable fit-to-page.
Use the paper edition that matches the printer tray.