


Paper bell ornament

pap-068 / A4 / Parts overview - NOT A CUTTING SHEET

USE THE FOLLOWING PATTERN SHEETS AT ACTUAL SIZE.

These miniature views identify the supplied patterns; they are deliberately reduced.




1. Pattern 1

2. Pattern 2

2 pattern sheets supplied. Printed details are not cut lines unless explicitly marked.

Solid cut boundary / dashed score / shaded joining area. Read the full instructions.

Dry-fit the parts before gluing. Keep this overview beside the full-size pattern sheets.




Print at actual size / 100%. Disable fit-to-page.
Use the paper edition that matches the printer tray.

Paper bell ornament

pap-068 / A4 / Pattern 1

Main cone sector




Print at actual size / 100%. Disable fit-to-page.
Use the paper edition that matches the printer tray.

Paper bell ornament

pap-068 / A4 / Pattern 2

Bell handle and clapper



Print at actual size / 100%. Disable fit-to-page.
Use the paper edition that matches the printer tray.

Paper bell ornament

pap-068 / A4 / Instructions

PURPOSE

Paper bell ornament developed as a measured original paper study. The packet provides the actual parts, joining or shaping marks, drawing dimensions and an assembly sequence. Print at actual size and dry-fit the parts before gluing.

DRAWING FACTS

- Cone sector radius: 77 mm; angle 240 degrees; joining tab 7 mm.
- Ideal paper-surface cone: base diameter 102.67 mm and height 57.39 mm before material/adhesive effects.

MATERIALS


Plain 100 to 140 gsm paper for a first dimensional trial; approximately 160 to 220 gsm card only after confirming the folds. Use a ruler, suitable scissors, a blunt scoring tool and a small amount of paper adhesive. An adult should handle internal cuts, holes and small fasteners.

HOW TO USE THESE PAGES

1. Cut the cone sector with its seam tab attached. Score the seam hinge and gently curl the sector.
2. Overlap the plain radial edge onto the shaded tab, aligning the pointed end and curved rim endpoints. Glue the seam and let it dry.
3. Cut the separate ring, clapper disc and fixing strip. Glue one strip end behind the clapper and the other inside the cone so the disc hangs below the rim.
4. Attach the paper ring at the cone tip with a small separate paper fixing strip. Support the bell while checking the joins; it is a display bell without a working striker.

LIMITS AND CHECKS

- Drawing dimensions describe flat paper surfaces, not verified internal capacity, load strength, fit or material compatibility.
- No mailing, food-contact, archival, toy-safety, protective-wear or cutting-machine certification is supplied.
- Make a plain-paper trial first; paper thickness and fold accuracy can change the fit.
- Trial: Measure the 50 mm reference and two named component dimensions.
- Trial: Make a complete empty trial and document fold direction, joining order, collision, stability and any fragile features.
- Trial: Repeat the trial using your chosen paper. Check that every join holds and each moving part works freely before decorating.



50 mm print check

Print at actual size / 100%. Disable fit-to-page.

Use the paper edition that matches the printer tray.