


Paper snail spiral shell


pap-142 / LETTER / Parts overview - NOT A CUTTING SHEET

USE THE FOLLOWING PATTERN SHEETS AT ACTUAL SIZE.

These miniature views identify the supplied patterns; they are deliberately reduced.



1. Pattern 1




2. Pattern 2

2 pattern sheets supplied. Printed details are not cut lines unless explicitly marked.

Solid cut boundary / dashed score / shaded joining area. Read the full instructions.

Dry-fit the parts before gluing. Keep this overview beside the full-size pattern sheets.




Print at actual size / 100%. Disable fit-to-page.
Use the paper edition that matches the printer tray.

Paper snail spiral shell

pap-142 / LETTER / Pattern 1

Spiral shell




Print at actual size / 100%. Disable fit-to-page.
Use the paper edition that matches the printer tray.

Paper snail spiral shell

pap-142 / LETTER / Pattern 2

Snail body



Print at actual size / 100%. Disable fit-to-page.
Use the paper edition that matches the printer tray.

Paper snail spiral shell

pap-142 / LETTER / Instructions

PURPOSE

Paper snail spiral shell developed as a measured original paper study. The packet provides the actual parts, joining or shaping marks, drawing dimensions and an assembly sequence. Print at actual size and dry-fit the parts before gluing.

DRAWING FACTS

- Component sizes are shown on each pattern; these are original folded/assembled craft studies.

MATERIALS

Plain 100 to 140 gsm paper for a first dimensional trial; approximately 160 to 220 gsm card only after confirming the folds. Use a ruler, suitable scissors, a blunt scoring tool and a small amount of paper adhesive. An adult should handle internal cuts, holes and small fasteners.

HOW TO USE THESE PAGES

1. Cut the shell disc and body, then follow the spiral cut from its outer end toward the center pad.
2. Roll the strip loosely from its outside end to form a raised spiral, and glue the lowest turn to the remaining center pad.
3. Attach the shell to the indicated body region after a dry-fit, keeping antennae unsupported by heavy parts.
4. Record the actual coil relief and stability; the finished shell depth depends on the paper and rolling tension.

LIMITS AND CHECKS

- Drawing dimensions describe flat paper surfaces, not verified internal capacity, load strength, fit or material compatibility.
- No mailing, food-contact, archival, toy-safety, protective-wear or cutting-machine certification is supplied.
- Make a plain-paper trial first; paper thickness and fold accuracy can change the fit.
- Trial: Measure the 50 mm reference and two named component dimensions.
- Trial: Make a complete empty trial and document fold direction, joining order, collision, stability and any fragile features.
- Trial: Repeat the trial using your chosen paper. Check that every join holds and each moving part works freely before decorating.



50 mm print check

Print at actual size / 100%. Disable fit-to-page.

Use the paper edition that matches the printer tray.