

Scalloped napkin wrap pattern

par-073 / A4 / Parts overview - NOT A CUTTING SHEET

USE THE FOLLOWING PATTERN SHEETS AT ACTUAL SIZE.

These miniature views identify the supplied patterns; they are deliberately reduced.




1. Pattern 1

1 pattern sheet supplied. Printed details are not cut lines unless explicitly marked.

Solid cut boundary / dashed score / shaded joining area. Read the full instructions.

Dry-fit the parts before gluing. Keep this overview beside the full-size pattern sheets.



Print at actual size / 100%. Disable fit-to-page.
Use the paper edition that matches the printer tray.

Scalloped napkin wrap pattern

par-073 / A4 / Pattern 1

Napkin wrap



Print at actual size / 100%. Disable fit-to-page.
Use the paper edition that matches the printer tray.

Scalloped napkin wrap pattern

par-073 / A4 / Instructions

PURPOSE

Scalloped napkin wrap pattern developed as a measured original paper study. The packet provides the actual parts, joining or shaping marks, drawing dimensions and an assembly sequence. Print at actual size and dry-fit the parts before gluing.

DRAWING FACTS

- 175 mm-long paper wrap with an 18 mm overlap and a scalloped upper edge.

MATERIALS

Plain 100 to 140 gsm paper for a first dimensional trial; approximately 160 to 220 gsm card only after confirming the folds. Use a ruler, suitable scissors, a blunt scoring tool and a small amount of paper adhesive. An adult should handle internal cuts, holes and small fasteners.

HOW TO USE THESE PAGES

1. Cut the band around its complete outer contour. Keep the shaded overlap attached.
2. Wrap the band loosely around the actual folded napkin, bringing the plain end over the 18 mm shaded area. Dry-fit before applying adhesive.
3. Glue only paper to paper at the overlap, keeping the adhesive off the napkin. Support the ring until the seam holds.
4. Let it dry completely, then check that the napkin slides out easily. Keep the printed paper separate from food.

LIMITS AND CHECKS

- Drawing dimensions describe flat paper surfaces, not verified internal capacity, load strength, fit or material compatibility.
- No mailing, food-contact, archival, toy-safety, protective-wear or cutting-machine certification is supplied.
- Make a plain-paper trial first; paper thickness and fold accuracy can change the fit.
- Trial: Measure the 50 mm reference and two named component dimensions.
- Trial: Make a complete empty trial and document fold direction, joining order, collision, stability and any fragile features.
- Trial: Repeat the trial using your chosen paper. Check that every join holds and each moving part works freely before decorating.



50 mm print check

Print at actual size / 100%. Disable fit-to-page.
Use the paper edition that matches the printer tray.